L.V. Lomas Ltd 99 Summerlea Rd Brampton; Ontario; L6T 4V2 Canada



PRODUCT: Celite 545

CODE: CJM115



Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER...... CELITE CORPORATION P.O. BOX 371725 **PITTSBURGH** USA 15251-7725

PRODUCT NAME..... PRODUCT CODE(S)..... Celite 545 CJM115 MATERIAL USE

24 HOUR EMERGENCY NUMBER: CALL Newalta Industrial Services 1-800-567-7455.

Continuo 02. COMPOCITION/INFORMATION ON INCORPORTATIO

Section 02: COMPOSITION/INFORMATION ON INGREDIENTS					
Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
Flux Calcined Diatomite	100	Not Indicated	68855-54-9	Not Indicated	Not Indicated
Cristobalite	<50	Not Indicated	14464-46-1	Not Indicated	Not Indicated
Crystalline Silica - Quartz	<4	0.1 mg/m3	14808-60-7	> 8000 mg/kg Oral Rat	Not Indicated

Section 03: HAZARDS IDENTIFICATION

Eye contact. Skin contact. Inhalation. Ingestion. SKIN CONTACT..... May cause skin irritation. Avoid skin contact. EYE CONTACT..... May cause eye irritation. Avoid eye contact. INGESTION..... No adverse health expected to develop. INHALATION.

EXPOSURE

May cause irritation of nose, throat or respiratory tract. Avoid inhalation. MEDICAL CONDITIONS AFFECTED BY Pre-existing respiratory disease may be aggrevated by this material.

SIGNS OF OVER EXPOSURE...... Prolonged, excessive exposure to dust may cause chronic pulmonary disease.

Section 04: FIRST AID MEASURES

EYE CONTACT..... Immediately hold eyelids open and flush with water for at least 15 minutes. If irritation develops or persists, seek medical attention. Wash affected area immediately with large amounts of soap and water. If irritation SKIN CONTACT..... develops or persists, seek medical attention. INHALATION..... Move victim to fresh air. If breathing has stopped, perform artificial respiration. If breathing is difficult, administer oxygen. In all cases of doubt, or when symptoms persist, seek medical attention. INGESTION..... DO NOT induce vomiting. Drink 1 or 2 glasses of water. If necessary, seek medical attention. NOTES TO PHYSICIAN..... Treat symptomatically.

Section 05: FIRE FIGHTING MEASURES

FLASH POINT (°C), METHOD.....AUTO IGNITION TEMPERATURE (°C)..... Not flammable. Not applicable. UPPER FLAMMABLE LIMIT (% VOL)........ LOWER FLAMMABLE LIMIT (% VOL)...... Not applicable. Not applicable. FLAMMABILITY.... Com I. HAZARDOUS COMBUSTION PRODUCTS... Not applicable.

UNUSUAL FIRE / EXPLOSION HAZARDS...

Avoid high dust concentrations. Assure all equipment is properly grounded to prevent static discharges, and vented to provide for potential energy release. Avoid heat, sparks and open flames.

SENSITIVITY TO MECHANICAL IMPACT.... Not sensitive.

Dust suspended in air in critical proportions and in the presence of an ignition source may SENSITIVITY TO STATIC DISCHARGE...... cause explosion. EXTINGUISHING MEDIA.....

Water spray, foam, dry powder or carbon dioxide.

00001759	MATERIAL SAFETY DATA SHEET	Page 2					
PRODUCT: Celite 545	CODE:	CJM115					
Section	05: FIRE FIGHTING MEASURES						
SPECIAL FIRE FIGHTING PROCEDURES	Firefighters should wear protective equipment as required.						
Section 06:	ACCIDENTAL RELEASE MEASURES						
LEAKS AND SPILLS	Vaccum/shovel up and transfer into a drum for reuse or disposal. Do not enter sewers or waterways. Wear protective clothing during cleanup.	allow product to					
Section	07: HANDLING AND STORAGE						
HANDLING PROCEDURES	ingestion. Avoid dusting when handling and avoid all possible sources of flame). Wash skin thoroughly after handling and before eating or smoking industrial hydiene practices in handling this material.	ignition (spark or					
STORAGE NEEDS	Keep container tightly closed Store in a cool, dry, well-ventilated area.						
Section 08: EXPO	Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION						
VENTILATION REQUIREMENTS PROTECTIVE EQUIPMENT EYE/TYPE RESPIRATORY/TYPE GLOVES/ TYPE CLOTHING/TYPE FOOTWEAR/TYPE BODY/TYPE	Wear saftey glasses with side shields or goggles. A NIOSH/OSHA approved dust respirator should be worn. Determine the by consulting the respirator manufacturer. Wear protective gloves. No special protective clothing is required. No special footwear is required.	e appropriate type					
	HYSICAL AND CHEMICAL PROPERTIES	***************************************					
PHYSICAL STATE ODOUR ODOUR THRESHOLD (ppm) SPECIFIC GRAVITY VAPOUR DENSITY (AIR=1) VAPOUR PRESSURE (mm Hg) EVAPORATION RATE BOILING POINT (°C) pH SOLUBILITY IN WATER (% WW) VISCOSITY COEFFICIENT OF WATER\OIL DISTRIBUTION FREEZING POINT (°C) MELTING POINT (°C) % VOLATILE	Fine. White. Powder. Odourless. Not available. 2.3. water = 1. Not applicable. Not applicable. Not applicable. Not applicable. Not applicable. Not applicable. Solution of available. Not available. Not available. Not applicable. Not applicable. Not applicable. Not determined. Nil.						
Section 1	0: STABILITY AND REACTIVITY						
HAZARDOUS POLYMERIZATIONSTABILITYINCOMPATIBILITYCONDITIONS TO AVOIDHAZARDOUS PRODUCTS OF DECOMPOSITION	Hydrofluoric acid. Avoid generating dust. Avoid heat and any source of ignition.						
Section 11:	TOXICOLOGICAL INFORMATION						
	May cause slight respiratory irritation. May cause eye irritation. May cause respiratory tract. Prolonged exposure can cause pulmonary disease. IARC Group 1. No evidence of teratogen effects. No evidence of mutagenic effects.	e irritation to					

00001759	MATERIAL SAFETY DATA SHEET	Page
PRODUCT: Celite 545	*	CODE: CJM115
Section	12: ECOLOGICAL INFORMATION	
ECOTOXICITY DATAPRODUCTS OF DEGRADATIONBIODEGRADABILITY	Environmentally inert.	
Section	13: DISPOSAL CONSIDERATIONS	
WASTE DISPOSAL	Dispose in a suitable waste treatment facility in local regulations.	compliance with all federal, provincial and
Section	14: TRANSPORT INFORMATION	
TDG CLASSIFICATION	Not regulated under TDG (Canada).	
Section	15: REGULATORY INFORMATION	
CEPA STATUSWHMIS CLASSIFICATION	All the ingredients are on the DSL list. WHMIS Class D2A: Materials Causing Other To	oxic Effects-Very Toxic Material.
Section	on 16: OTHER INFORMATION	
REFERENCES TELEPHONE NUMBER:PREPARED BY: PREPARATION DATE:	Regulatory Affairs	